

LATTICE TOWERS

Floodlight towers

DATASHEET

Product nr.
Ref. nr.
Latest rev.

S 2 30,0M-50
05.01.03.02.25
21.10.2020



Series 2

30,0 m

The given tower is designed as an equilateral triangle, with a fully welded steel lattice, composed by legs and bracing made of solid round bars.

Lamp brackets are mounted on the top of the tower and have the possibility to install up to 8 lamps.

Total theoretical mast weight ($\pm 10\%$) (excluding the lamp brackets) = 1132 kg

Leg distance at tower base = 1000 mm

All the steel is hot dip galvanized and is designed according to DS/EN ISO 1461.

Application:

The mast can be used in accordance with the standard LTR 6000 series for brackets, suitable for standard lamp types, such as Siteco A3 Maxi and FL20 Maxi and Phillips 20 Optivision.

Number of lamps	6	8
Lamp brackets	LT-06-00	LT-08-00
Wind drag area, A_w	0,99 m ²	1,31 m ²
Weight	174 kg	245 kg

The values shown in the table are calculated according to EN 1993-3-1 + NA - Design of Steel Structures – Towers and Masts. A_w is wind drag area incl. form factor.

Foundation types:

The following foundation solutions can be used with the mast:

Foundation	Block foundation for casting on site	Prefabricated dig-in foundations	Steel foundation for dig-in solutions	Movable foundations, normally for temporary sites	Bedrock anchoring
Type	F305	PF305	-	FF305	FA305

