

FREESTANDING LATTICE TOWERS

DATA SHEET

TRIANGULAR TOWER

Product no.

S O 12,0M-00

Ref. nr.

01.01.01.01.20

Latest rev.

06.07.2020



Series 0

12,0 m

The given tower is designed as an equilateral triangle, with a fully welded steel lattice structure, composed by legs and bracings made of solid round bars.

The top pole is mounted with pin steel bolts.

The standard top pole is composed of 3.0 m. circular steel tube $\varnothing 60,3 \times 3,65$ mm. Other types of top poles can be mounted, if necessary.

The steel is hot dip galvanized according to BS/EN ISO 1461.

Total theoretical tower weight ($\pm 10\%$) (excluding the top pole) = 151 kg

Leg distance at tower base = 400 mm

Foundation bolts = 6 x M16

The design of the lattice tower is according to: BS/EN 1993-3-1 – Design of steel structures – Towers, masts and chimneys. BS/EN 1991-1-4 – Actions on structures – Wind actions.

Tower bearing capacity (A_w)	In most areas up to Northern Scotland	In most areas up to Southern Scotland	In most areas in England, Cornwall and Wales
Open land, flat land without obstacles (TC I)	0.14 m ²	Not applicable for the area	Not applicable for the area
Terrain with hedges, agricultural areas (TC II)	0.24 m ²	Not applicable for the area	Not applicable for the area
Suburbs, industrial or commercial areas (TC III)	0.50 m ²	0.30 m ²	0.10 m ²

A_w is the maximum total wind drag area incl. shape factor that can be installed with center 1.25 m. above tower top.

Foundation types:

The following foundation solutions can be used with the tower:

Foundation	Block foundation for casting on site	Prefabricated dig-in foundations	Steel foundation for dig-in solutions	Movable foundations, normally for temporary sites	Bedrock anchoring
Type	F301	PF301	SF301	FF301	FA301

