

# FREESTANDING LATTICE TOWERS

## DATA SHEET

### TRIANGULAR TOWER

Product no. S 2 37,50M-00  
 Ref. nr. 01.02.01.02.50  
 Latest rev. 15.10.2018



## Series 2

### 37,5 m

The given tower is designed as an equilateral triangle, with a fully welded steel lattice structure, composed by legs and bracings made of solid round bars.

The top pole is mounted with pin steel bolts.

The standard top pole is composed of 3.0 m. circular steel tube  $\varnothing 60,3 \times 3,65$  mm. Other types of top poles can be mounted, if necessary.

The steel is hot dip galvanized according to BS/EN ISO 1461.

Total theoretical tower weight ( $\pm 10\%$ ) (excluding the top pole) = 1700 kg

Leg distance at tower base = 1150 mm

Foundation bolts = 15 x M24

The design of the lattice tower is according to: BS/EN 1993-3-1 – Design of steel structures – Towers, masts and chimneys. BS/EN 1991-1-4 – Actions on structures – Wind actions.

#### Foundation types:

The following foundation solutions can be used with the tower:

Foundation	Block foundation for casting on site	Prefabricated dig-in foundations	Steel foundation for dig-in solutions	Movable foundations, normally for temporary sites	Bedrock anchoring
Type	F306	PF306	-	FF306	FA306

